


\* MALE ROD END SHOWN See sheet 4 for male & female variations and dimensions

⊗ Single Slotted CUSH. ADJ.  
 ⊗ Cross Slotted CUSH. Relief (Fixed)

CYLINDER SIZE	ROD DIA. E E	E	CB	D	A	AA	B	F	H BSPP.	J	K	R	P	Q	RR	S
HB 15 1.50" BORE	0.625" STD. 15.87	0.63" 15.87	6.00" 152.4	2.00" 50.8	5.00"	2.50"	2.88"	0.38"	1/2"	1.75"	1.50"	0.50"	1.63"	4.25"	0.44"	3.44"
	1.000" 25.4	1.00" 25.4	6.38" 161.92	2.38" 60.32	127.0	63.5	73.02	9.52		44.45	38.1	12.7	41.4	107.95	11.11	87.31
HB 20 2.00" BORE	1.000" STD. 25.4	0.75" 19.05	6.63" 168.27	2.38" 60.32	5.25"	3.00"	2.88"	0.62"	1/2"	1.75"	1.50"	0.63"	2.05"	5.13"	0.56"	4.13"
	1.375" 34.92	1.00" 25.4	6.88" 174.62	2.63" 66.68	133.35	76.2	73.02	15.87		44.45	38.1	15.87	52.07	130.17	14.28	104.77
HB 25 2.50" BORE	1.000" STD. 25.4	0.75" 19.05	6.75" 171.45	2.38" 60.32	5.38"	3.50"	3.00"	0.62"	1/2"	1.75"	1.50"	0.63"	2.55"	5.63"	0.56"	4.63"
	1.375" 34.92	1.00" 25.4	7.00" 177.8	2.63" 66.68												
	1.750" 44.45	1.25" 31.75	7.25" 184.15	2.88" 73.02												
HB 32 3.25" BORE	1.375" STD. 34.92	0.88" 22.22	7.88" 200.02	2.75" 69.85	6.25"	4.50"	3.50"	0.75"	3/4"	2.00"	1.75"	0.75"	3.25"	7.13"	0.69"	5.88"
	1.750" 44.45	1.13" 28.57	8.13" 206.37	3.00" 76.2												
	2.000" 50.8	1.25" 31.75	8.25" 209.55	3.13" 79.38												
HB 40 4.00" BORE	1.750" STD. 44.45	1.00" 25.4	8.50" 215.9	3.00" 76.2	6.63"	5.00"	3.75"	0.88"	3/4"	2.00"	1.75"	0.75"	3.82"	7.63"	0.69"	6.38"
	2.000" 50.8	1.13" 28.57	8.63" 219.07	3.13" 79.37												
	2.500" 63.5	1.38" 34.92	8.88" 225.42	3.38" 85.73												
HB 50 5.00" BORE	2.000" STD. 50.8	1.13" 28.57	9.13" 231.77	3.13" 79.37	7.13"	6.50"	4.25"	0.88"	3/4"	2.00"	1.75"	1.06"	4.95"	9.75"	0.94"	8.19"
	2.500" 63.5	1.38" 34.92	9.38" 238.13	3.38" 85.73												
	3.000" 76.2	1.38" 34.92	9.38" 238.13	3.38" 85.73												
	3.500" 88.9	1.38" 34.92	9.38" 238.13	3.38" 85.73												
HB 60 6.00" BORE	2.500" STD. 63.5	1.25" 31.75	10.63"	3.50"	8.38"	7.50"	4.88"	1.00"	1.00"	2.25"	2.25"	1.12"	5.73"	11.25"	1.06"	9.44"
	3.000" 76.2	1.25" 31.75														
	3.500" 88.9	1.25" 31.75														
	4.000" 101.6	1.25" 31.75														
HB 70 7.00" BORE	3.000" STD. 76.2	1.25" 31.75	11.75"	3.81"	9.50"	8.50"	5.38"	1.00"	1,1/4"	2.75"	2.75"	1.25"	6.58"	12.63"	1.19"	10.63"
	3.500" 88.9	1.25" 31.75														
	4.000" 101.6	1.25" 31.75														
	5.000" 127.0	1.25" 31.75														
HB 80 8.00" BORE	3.500" STD. 88.9	1.25" 31.75	12.75"	3.94"	10.50"	9.50"	6.13"	1.00"	1,1/2"	3.00"	3.00"	1.38"	7.50"	14.00"	1.31"	11.81"
	4.000" 101.6	1.25" 31.75														
	5.000" 127.0	1.25" 31.75														
	5.500" 139.7	1.25" 31.75														

STYLE 5  
CAP  
SQUARE FLANGE



\* MALE ROD END SHOWN See sheet 4A for male & female variations and dimensions

-  Single Slotted CUSH. ADJ.
-  Cross Slotted CUSH. Relief (Fixed)

CYLINDER SIZE	ROD DIA. E E	E	C B	D	HH Ø	A	AA	B	H	J	R	Q	SU	IQ	E B Ø
HB 100 10.00" BORE	4.50" 114.3	2.94" 74.6	15.06" 382.57	4.75" 120.65	8.25" 209.55	12.13"	12.63"	8.50"	2.00"	3.69"	1.56"	16.63"	14.13"	9.89"	1.31"
	5.00" STD. 127.0	3.19" 80.95	15.31" 388.93	5.00" 127.0	8.75" 222.25										
	5.50" 139.7	3.19" 80.95	15.31" 388.93	5.00" 127.0	9.38" 238.13										
	7.00" 177.8	3.50" 88.9	15.63" 396.87	5.31" 134.93	10.5" 266.7										
HB 120 12.00" BORE	5.50" 139.7	3.19" 80.95	17.69" 449.25	5.44" 138.09	9.38" 238.13	14.5"	14.88"	10.00"	2.50"	4.44"	2.09"	19.75"	16.79"	11.75"	1.56"
	7.00" STD. 177.8	3.50" 88.9	18.0" 457.20	5.75" 146.05	10.5" 266.7										
	8.00" 203.2	4.00" 101.6	18.5" 469.90	6.25" 158.75	12.5" 317.5										